

SERVICE BULLITON

Date: 5/15/03
To: ALL POWERTRAMP CUSTOMERS
From: Extreme Concepts
RE: Service Bulliton

All PowerTramp units shall use 1/4 inch R R W -410 steel galvanized wire rope as per the PowerTramp maintenance manual. All cables shall be changed at first sign of wear . New cables are available from Extreme Concepts or a certified rigging supply store.

All cables on the winch shall be wrapped 3 times around drum after securing the cable to the winch drum.

At this time, Extreme Concepts can not endorse the use of 3-inch webbing, until more testing is done.

If you are currently using webbing at this time, Please contact Extreme Concepts and we will send replacement cables out>

If you have any question please call:



Tony Wolfe

Extreme Concepts

Extreme Concepts

Service Bulletin

To: All PowerTramp users**From:** Tony Wolfe**Fax:****Pages:****Phone:****Date:** 05/07/03**Re:****CC:****Power****Tramp**

Urgent For Review Please Comment Please Reply Please Recycle

• Comments:

At this time Extreme Concepts informs all PowerTramp users the following:

The PowerTramp unit designed and manufactured by Extreme Concepts wants all operators to be informed.

The Shock cord tubing (size ¼ by 1/8) weight limit is 20 lbs. per shock cord if you place a rider 180 lbs. you will need to add 1 more cord for a total of 9 shock cords on each side of rider

The service manual it states 8 shock cords per side.

Please be aware of the mistake and add this page to your service manual

Thanks


Tony Wolfe

Extreme Concepts